



SLV External/Internal

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Date of issue: 2016/05/17

Revision date: 2017/10/18

Supersedes: 2016/12/14

Version: 3.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Trade name : SLV External/Internal
Product group : Trade product

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Professional use, Industrial use
Industrial/Professional use spec : Common cements and cement containing mixtures (hydraulic binders) are used industrially, by professionals in building and construction work, indoor and/or outdoor
The identified uses of cements and cement containing mixtures cover the dry products and the products in a wet suspension (paste).
Use of the substance/mixture : Fire protection of structures in steel, concrete and wood, indoor or outdoor
Function or use category : Flame retardants and fire preventing agents

1.2.2. Uses advised against

Restrictions on use : Any other intended applications should be discussed with the manufacturer

1.3. Details of the supplier of the safety data sheet

Manufacturer

Nestaan NV
Rue du Bois des Hospices 2
B- 7522 Blandain

Tel.: +32(0)69.77.83.20
www.nestaan.be

Contact person:
Frédérique van Nes - infonestaan@nhb.be

1.4. Emergency telephone number

Emergency number : Anti-poison Center
Belgium: + 32 (0)70 245 245

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Skin corrosion/irritation, Category 2 H315
Serious eye damage/eye irritation, Category 1 H318
Skin sensitisation, Category 1 H317
Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation H335

Full text of H-statements see section 16.

Adverse physicochemical, human health and environmental effects

Causes skin irritation. May cause an allergic skin reaction. Causes serious eye damage. May cause respiratory irritation.

SLV External/Internal

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Version: 3.0

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



Signal word (CLP)

Hazardous ingredients

Hazard statements (CLP)

Precautionary statements (CLP)

- : Danger
- : Portland cement
- : H315 - Causes skin irritation.
H317 - May cause an allergic skin reaction.
H318 - Causes serious eye damage.
H335 - May cause respiratory irritation.
- : P261 - Avoid breathing dust, spray.
P280 - Wear eye protection, protective clothing, protective gloves.
P264 - Wash hands, forearms and face thoroughly after handling.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 - Immediately call a POISON CENTER/doctor
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.

2.3. Other hazards

Other hazards not contributing to the classification

- : Skin contact with wet cement, fresh concrete or mortar may cause irritation, dermatitis or burns. May cause damage to products made of aluminium or other non-noble metals. Cement is either naturally low in soluble chromium VI or reducing agents have been added to control the levels of sensitising soluble chromium (VI) to below 2mg/kg (0.0002%) of the total dry weight of the cement ready for use according to legislation specified under Section 15.

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Comments

- : <1% Silica, respirable crystalline
Does not contain: Asbestos
Do not contain soluble chromium VI (in excess of 2 ppm)

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Portland cement	(CAS-No.) 65997-15-1 (EC-No.) 266-043-4	30 - 50	STOT SE 3, H335 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317
vermiculite	(CAS-No.) 1318-00-9 (EC-No.) 603-518-0	20 - 50	Not classified

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures general : If you feel unwell, seek medical advice. First aid workers should avoid contact with wet cement or wet cement containing mixtures.
- First-aid measures after inhalation : Remove victim to fresh air. Call a POISON CENTER/doctor. In case of irritation or coughing : Get medical advice/attention.
- First-aid measures after skin contact : For dry cement, remove and rinse abundantly with water. For wet cement, wash skin with plenty of water. Take off immediately all contaminated clothing and wash it before reuse. If irritation persists, consult a doctor. In case of burns: Get immediate medical advice/attention.
- First-aid measures after eye contact : In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Immediately flush eyes thoroughly with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor.
- First-aid measures after ingestion : Immediately call a POISON CENTER/doctor. If swallowed, rinse mouth with water (only if the person is conscious). Drink plenty of water. Do not induce vomiting.

SLV External/Internal

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Version: 3.0

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/effects after inhalation : May cause respiratory irritation. Inhalation:dust,mist. By prolonged exposure : Lung tissue affection/degeneration.
- Symptoms/effects after skin contact : Contact during a long period may cause light irritation. Prevent moisture contact. Causes skin irritation. Dermatitis.
- Symptoms/effects after eye contact : Possible risk of irreversible effects.

4.3. Indication of any immediate medical attention and special treatment needed

Never give anything by mouth to an unconscious person. Avoid contact with wet product.

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Adapt extinguishing media to the environment.
- Unsuitable extinguishing media : Do not use water jet to extinguish.

5.2. Special hazards arising from the substance or mixture

- Fire hazard : Non combustible.
- Explosion hazard : Not applicable.
- Reactivity in case of fire : None under normal conditions.
- Hazardous decomposition products in case of fire : None known.

5.3. Advice for firefighters

- Precautionary measures fire : Exposure to fire/heat: keep upwind.
- Firefighting instructions : Cool tanks/drums with water spray/remove them into safety.
- Protection during firefighting : No fire hazard.
- Other information : Avoid dust formation. Avoid release to the environment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Avoid contact with skin and eyes. Avoid dust formation. Inhalation of dust. Ensure adequate air ventilation. Refer to chapter 8.

6.1.1. For non-emergency personnel

- Protective equipment : For further information refer to section 8: "Exposure controls/personal protection".
- Measures in case of dust release : In case of dust production: keep upwind. Dust production: have neighbourhood close doors and windows.

6.1.2. For emergency responders

- Protective equipment : For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

- For containment : Plug the leak, cut off the supply. Knock down/dilute dust cloud with water spray. Clean up immediately by sweeping or vacuum.
- Methods for cleaning up : Powdered: do not use compressed air for pumping over spills. Clean up immediately by sweeping or vacuum. Scoop solid spill into closing containers. Stop dust cloud by humidifying with water. Wash down leftovers with plenty of water. Let solidify.
- Other information : Avoid dust formation.

6.4. Reference to other sections

Reference to other sections (8, 13). SECTION 7.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Additional hazards when processed : None under normal use.
- Precautions for safe handling : Thoroughly clean/dry the installation before use. Avoid raising dust. Keep container tightly closed. Ensure good ventilation of the work station. Additional good practice advice. <http://www.nepsi.eu/good-practice-guide>. These good practices have been adopted under the Social Dialogue "Agreement on Workers' Health Protection through the Good Handling and Use of Crystalline Silica and Products Containing it by Employee and Employer European sectoral associations, among which CEMBUREAU.
- Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Handle in accordance with good industrial hygiene and safety practice.

SLV External/Internal

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Version: 3.0

7.2. Conditions for safe storage, including any incompatibilities

Technical measures	: Use grounded electrical/mechanical equipment.
Storage conditions	: Store in a well-ventilated place. Protect against frost. Do not stack pallets on each other. Packed products should be stored in unopened bags clear of the ground in cool, dry conditions and protected from excessive draught in order to avoid degradation of quality. Bags should be stacked in a stable manner. Do not use aluminium containers for the storage or transport of wet cement containing mixtures due to incompatibility of the materials.
Incompatible products	: Keep away from reducing agents/(strong) acids /(strong) bases. Moisture.
Incompatible materials	: Refer to Section 10 on Incompatible Materials.
Heat and ignition sources	: Protect from heat and direct sunlight.
Information on mixed storage	: Segregate from foodstuffs. oxidizing agents. (strong) acids. water/moisture.
Storage area	: Store in a dry area. Keep out of direct sunlight.
Special rules on packaging	: watertight;dry,clean;correctly labelled;Meet the legal requirements

7.3. Specific end use(s)

For the relevant identified use(s) listed in Section 1 the advice mentioned in this section 7 is to be observed.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

SLV External/Internal		
EU	IOELV STEL (mg/m ³)	10 mg/m ³ respirable dust
Portland cement (65997-15-1)		
EU	IOELV TWA (mg/m ³)	10 mg/m ³ respirable dust
vermiculite (1318-00-9)		
EU	IOELV STEL (mg/m ³)	10 mg/m ³ respirable dust

Additional information : European Union Legislation. In the event that dust and/or fine particles are generated with this product, it is prudent to minimize prolonged inhalation exposure to these forms not to exceed the occupational exposure limit.

8.2. Exposure controls

Appropriate engineering controls:

General exposure limit for inhalable particulate matter. If possible with source exhaust and good ventilation.

Personal protective equipment:

Safety glasses. Dust formation: dust mask. Gloves. protective clothing.

Hand protection:

Chemical resistant PVC gloves (to European standard EN 374 or equivalent). Use watertight, wear- and alkali-resistant protective gloves (eg nitrile soaked cotton gloves with CE marking) internally lined with cotton; boots; closed long-sleeved protective clothing as well as skin care products (eg barrier creams) to protect the skin from prolonged contact with wet cement. Particular care should be taken to ensure that wet cement does not enter the boots. For the gloves, respect the maximum wearing time to avoid skin problems. In some circumstances, such as when laying concrete or screed, waterproof trousers or kneepads are necessary. Supplementary note: The specifications are based on tests, literature data and information of glove manufacturers or are derived from similar substances by analogy. Due to many conditions (e.g. temperature) it must be considered, that the practical usage of a chemical-protective glove in practice may be much shorter than the permeation time determined through testing

Eye protection:

Safety glasses with side-shields (frame goggles) (e.g. EN 166)

Skin and body protection:

Body protection must be chosen depending on activity and possible exposure, e.g. apron, protecting boots, chemical-protection suit (according to EN 14605 in case of splashes or EN ISO 13982 in case of dust)

Respiratory protection:

Ensure adequate ventilation. Dust formation: dust mask. Particle filter with medium efficiency for solid and liquid particles (e.g. EN 143 or 149, Type P2 or FFP2)



SLV External/Internal

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Version: 3.0

Thermal hazard protection:

On heating: self-contained breathing apparatus.

Environmental exposure controls:

Assure that emissions are compliant with all applicable air pollution control regulations. Refer to all applicable national, international and local regulations or provisions.

Other information:

Avoid contact with skin and eyes. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. During work avoid kneeling in fresh mortar or concrete wherever possible. If kneeling is absolutely necessary then appropriate waterproof personal protective equipment must be worn. Do not eat, drink or smoke when working with cement to avoid contact with skin or mouth. Before starting to work with cement, apply a barrier creme and reapply it at regular intervals. Immediately after working with cement or cement-containing materials, workers should wash or shower or use skin moisturisers. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Handle in accordance with good industrial hygiene and safety practice.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Solid
Appearance	: Powder.
Colour	: Grey.
Odour	: odourless.
Odour threshold	: not applicable, odour not perceivable
pH	: 11 - 12 Wet product:
Relative evaporation rate (butylacetate=1)	: Not applicable
Melting point	: ≈ 1500 °C
Freezing point	: Not applicable
Boiling point	: Not applicable
Flash point	: Not applicable
Auto-ignition temperature	: Not applicable
Decomposition temperature	: Not determined
Flammability (solid, gas)	: Not applicable
Vapour pressure	: Not applicable
Relative vapour density at 20 °C	: Not applicable
Relative density	: Not determined
Density	: 720 (SLV Ext) / 350-400 (SLV Int) cured form
Relative gas density	: Not determined
Solubility	: Poorly soluble in water. Water: 0,1 - 1,5 g/l Data apply to the main component
Log Pow	: Not determined
Viscosity, kinematic	: Not applicable
Viscosity, dynamic	: Not applicable
Explosive properties	: To our knowledge, this product does not present any particular risk, provided it is handled in accordance with good occupational hygiene and safety practice.
Oxidising properties	: Not applicable.
Explosive limits	: Not applicable

9.2. Other information

Minimum ignition energy	: Not applicable
Other properties	: If necessary, information on other physical and chemical parameters is indicated in this section.
Additional information	: No further information available.

SECTION 10: Stability and reactivity

10.1. Reactivity

Product - after addition of water, hardened condition: The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions. Wet cement is alkaline and incompatible with acids, with ammonium salts, with aluminium or other non-noble metals. Cement dissolves in hydrofluoric acid to produce corrosive silicon tetrafluoride gas. Cement reacts with water to form silicates and calcium hydroxide. Silicates in cement react with powerful oxidizers such as fluorine, boron trifluoride, chlorine trifluoride, manganese trifluoride, and oxygen difluoride.

SLV External/Internal

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Version: 3.0

10.3. Possibility of hazardous reactions

None under normal conditions. Polymerisation: none.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7). Avoid dust formation. Moisture.

10.5. Incompatible materials

acids and bases. Strong oxidizers. ammonium salts. Aluminium. aluminium powder. May cause damage to products made of aluminium or other non-noble metals.

10.6. Hazardous decomposition products

None under normal conditions.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (dermal) : Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (inhalation) : Not classified (Based on available data, the classification criteria are not met)

Portland cement (65997-15-1)

LD50 dermal rat	2000 mg/kg
Skin corrosion/irritation	: Causes skin irritation. pH: 11 - 12 Wet product:
Additional information	: Avoid prolonged and repeated contact with skin Contact during a long period may cause light irritation Prevent moisture contact May cause dermatitis by skin contact
Serious eye damage/irritation	: Causes serious eye damage. pH: 11 - 12 Wet product:
Respiratory or skin sensitisation	: May cause an allergic skin reaction.
Additional information	: By prolonged exposure : Lung tissue affection/degeneration
Germ cell mutagenicity	: Not classified (Based on available data, the classification criteria are not met)
Carcinogenicity	: Not classified (Based on available data, the classification criteria are not met)
Reproductive toxicity	: Not classified (Based on available data, the classification criteria are not met)
STOT-single exposure	: May cause respiratory irritation.
STOT-repeated exposure	: Not classified (Based on available data, the classification criteria are not met)
Aspiration hazard	: Not classified (Based on available data, the classification criteria are not met)
Potential adverse human health effects and symptoms	: Dust may cause mechanical irritation. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye damage. May cause respiratory irritation.
Other information	: When used and handled according to specifications, the product does not have any harmful effects according to our experience and the information provided to us.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Not classified as dangerous according to the criteria of Regulation (EC) No 1272/2008.
Ecology - air : Not classified as dangerous for the ozone layer (Regulation (EC) No 1005/2009).
Ecology - water : Do not allow the product to be released into the environment.
Acute aquatic toxicity : Not classified
Chronic aquatic toxicity : Not classified

Portland cement (65997-15-1)

LC50 fish 1	> 1000 mg/l (LC50; 96 h)
-------------	--------------------------

12.2. Persistence and degradability

SLV External/Internal

Persistence and degradability	The product has not been tested. The statement has been derived from the properties of the individual components.
-------------------------------	---

Portland cement (65997-15-1)

Persistence and degradability	Biodegradability: not applicable. No (test)data on mobility of the substance available.
-------------------------------	---

SLV External/Internal

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Version: 3.0

Portland cement (65997-15-1)	
Biochemical oxygen demand (BOD)	Not applicable
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable

12.3. Bioaccumulative potential

SLV External/Internal	
Log Pow	Not determined
Bioaccumulative potential	No bioaccumulation data available.

Portland cement (65997-15-1)	
Bioaccumulative potential	Bioaccumulation: not applicable.

12.4. Mobility in soil

SLV External/Internal	
Ecology - soil	Low mobility (soil). Data apply to the main component.

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

- Other adverse effects : When used and handled according to specifications, the product does not have any harmful effects according to our experience and the information provided to us.
- Additional information : No other effects known

SECTION 13: Disposal considerations

13.1. Waste treatment methods

- Regional legislation (waste) : Disposal must be done according to official regulations.
- Waste treatment methods : Collect all waste in suitable and labelled containers and dispose according to local legislation.
- Sewage disposal recommendations : Do not discharge into drains or the environment.
- Product/Packaging disposal recommendations : Remove waste in accordance with local and/or national regulations. Recycle/reuse. Precipitate/make insoluble. Remove to an authorized dump. Do not discharge into the sewer. Do not discharge into surface water. Obtain the consent of pollution control authorities before discharging to wastewater treatment plants.
- Additional information : Handle uncleaned empty containers as full ones. Empty containers should be taken for recycling, recovery or waste in accordance with local regulation.
- Ecology - waste materials : Disposal through controlled incineration or authorised waste dump. Dispose of in accordance with local laws/regulations. Avoid disposal in sewage systems. Dispose of the hardened product as a concrete waste. Due to the inert nature of concrete, concrete wastes are not considered as hazardous.

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

ADR	IMDG	IATA	ADN	RID
14.1. UN number				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.2. UN proper shipping name				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.3. Transport hazard class(es)				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.4. Packing group				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.5. Environmental hazards				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
No supplementary information available				

14.6. Special precautions for user

- Overland transport

Not regulated

- Transport by sea

Not regulated

- Air transport

Not regulated

SLV External/Internal

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Version: 3.0

- Inland waterway transport

Not regulated

- Rail transport

Not regulated

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Other information, restriction and prohibition regulations

: If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture. This does not in any way excuse the user from knowing and applying all the regulations governing his activity. It is the sole responsibility of the user to take all precautions required in handling the product. REACH annex XVII indicators. 1. Cement and cement-containing mixtures shall not be placed on the market, or used, if they contain, when hydrated, more than 2 mg/kg (0,0002 %) soluble chromium VI of the total dry weight of the cement.

2. If reducing agents are used, then without prejudice to the application of other Community provisions on the classification, packaging and labelling of substances and mixtures, suppliers shall ensure before the placing on the market that the packaging of cement or cement-containing mixtures is visibly, legibly and indelibly marked with information on the packing date, as well as on the storage conditions and the storage period appropriate to maintaining the activity of the reducing agent and to keeping the content of soluble chromium VI below the limit indicated in paragraph 1.

3. By way of derogation, paragraphs 1 and 2 shall not apply to the placing on the market for, and use in, controlled closed and totally automated processes in which cement and cement-containing mixtures are handled solely by machines and in which there is no possibility of contact with the skin.

4. The standard adopted by the European Committee for Standardization (CEN) for testing the water-soluble chromium (VI) content of cement and cement-containing mixtures shall be used as the test method for demonstrating conformity with paragraph 1.

15.1.2. National regulations

Users should ensure that they comply with any relevant local, provincial or national legislation.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Indication of changes:

Revised SDS according to Commission Regulation (EU) N°2015/830.

Section	Changed item	Change	Comments
4		Added	
9		Added	
10		Added	
12.		Added	
15		Added	

Abbreviations and acronyms:

ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level

SLV External/Internal

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Version: 3.0

DPD	Dangerous Preparations Directive 1999/45/EC
DSD	Dangerous Substances Directive 67/548/EEC
EC50	Median effective concentration
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
TLM	Median Tolerance Limit
vPvB	Very Persistent and Very Bioaccumulative

Data sources : Manufacturer/Supplier. ECHA reference. Authoring: . Quick.MSDS Sprl - Belgium
info@quickmsds.de +32 (0) 479 469 465.

Training advice : Normal use of this product shall imply use in accordance with the instructions on the packaging.

Other information : No further information available.

Full text of H- and EUH-statements:

Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H335	May cause respiratory irritation.

MSDS EU (REACH Annex II).

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product